

Ooma 2615W IP Phone

Enjoy efficient business communications using this high-end IP phone that features a suite of next-gen features including integrated Wi-Fi, Bluetooth support, 40 programmable buttons, an available extension module, dual Gigabit ports and a large 4.3 inch color LCD.



Features Supported

- Supports 10 lines
- Electronic Hook Switch (EHS) support for Bluetooth and DECT headsets
- Full-duplex speakerphone with HD audio to maximize audio quality and clarity
- 40 programmable keys
- Bluetooth
- 4.3" color display
- Dual-band Wi-Fi
- 10/100/1000 Ethernet with pass through port

Product Specifications

- **Protocols/Standards**
SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
- **Network Interfaces**
Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE
- **Bluetooth**
Integrated
- **Wi-Fi**
Integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4GHz & 5GHz)
- **Graphic Display**
4.3 inch (480x272) TFT color LCD
- **Voice Codecs and Capabilities**
Support for G7.29A/B, G.711 μ /a-law, G.726, G.722(wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF(in audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC
- **HD Audio**
HD handset and speakerphone with support for wideband audio
- **Extension Module**
Yes (GBX20)
- **Feature Keys**
10 line keys with up to 5 SIP accounts, 5 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: Message (with LED indicator), Transfer, Hold, Headset, Mute, Send/Redial, Speakerphone, Vol+, Vol-
- **Base Stand**
2 angle positions available, Wall Mountable (*wall mount sold separately)
- **QoS**
Layer 2 QoS (802.1Q, 802.1P) and Layer 3 QoS (ToS, DiffServ, MPLS)
- **Auxiliary Ports**
RJ9 headset jack (allowing EHS with Plantronics headsets), USB
- **Security**
User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot
- **Multi-language**
English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more
- **Upgrade/Provisioning**
Firmware upgrade via FTP / TFTP / HTTP / HTTPS, mass provisioning with GDMS (Grandstream Device Management System), TR-069 or AES encrypted XML configuration file
- **Power & Green Energy Efficiency**
Universal power adapter included:
Input: 100 - 240V; Output: +12VDC, 1A
Integrated Power-over-Ethernet (802.3af)
Max power consumption 6.3W (power adapter) or 7.4W (PoE)
- **Temperature and Humidity**
Operation: 0°C to 40°C, Storage: -10°C to 60°C
Humidity: 10% to 90% Non-condensing
- **Package Content**
Ooma 2615 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Start Guide, GPL license
- **Physical**
Dimension: Unit weight: 970g ; Package weight: 1480g
Dimension: 243mm x 210mm x 82.3mm
- **Compliance**
FCC: Part 15 Class B; Part 15 Subpart C, 15.247; Part 15 Subpart E, 15.407; FCC Part 68 HAC
CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 62368-1; EN 301489-1; EN 301489-17; EN 300328; EN 301893; EN 62311
RCM: AS/NZS CISPR32; AS/NZS 4268; AS/NZS 62368.1; AS/CA S004
IC: ICES-003; CS-03; RSS-247; RSS-102